

Professional rotary cultivator

417 S

NEW



Professional machine with power rating and features that recommend it for root crop harvesting and tillage duties on all terrain types. Combines exceptional ease of handling and versatility with the ability to work on all types of terrain safely, thanks to the self-locking differential and 5-speed gearbox.



The EHS system ensures ease of use, reduced effort and the maximum simplification for users.



Ergonomic differential locking lever and independent brakes supplied as standard.



Two power take-offs, one independent two-speed PTO and one synchronised PTO.

Power supply	Engine	Model	Displacement	Power*	Starting	Notes	Code
gasoline	POWERED by HONDA	GX 340 OHV	389 cm ³	10.7 HP	recoil start	multidisc clutch	68339100EN
gasoline	KOHLER	CH 395 OHV	277 cm ³	9.5 HP	recoil start/ electric	multidisc clutch/ battery supplied as standard	68339116EN
gasoline	KOHLER	CH 440 OHV	429 cm ³	14.0 HP	recoil start/ electric	mono-disc clutch/ battery supplied as standard	68339117EN
diesel	LOMBARDINI A KOHLER COMPANY	15LD440	441 cm ³	10.9 HP	recoil start	multidisc clutch	68339105EN
diesel	LOMBARDINI A KOHLER COMPANY	15LD440	441 cm ³	10.9 HP	recoil start/ electric	multidisc clutch/ battery supplied as standard	68339101EN
diesel	LOMBARDINI A KOHLER COMPANY	15LD440	441 cm ³	10.9 HP	recoil start/ electric	multidisc clutch/ lights/ battery supplied as standard	68339120EN
diesel	LOMBARDINI A KOHLER COMPANY	3LD510	505 cm ³	12.2 HP	recoil start	mono-disc clutch	68339102EN
diesel	LOMBARDINI A KOHLER COMPANY	3LD510	505 cm ³	12.2 HP	electric	mono-disc clutch/ battery supplied as standard	68339103EN
diesel	LOMBARDINI A KOHLER COMPANY	3LD510	505 cm ³	12.2 HP	electric	mono-disc clutch/ lights/ battery supplied as standard	68339104EN

* Engine power data refers to the values declared by each manufacturer. These values are calculated in accordance with specific measurement standards (such as SAE J1940, SAE J1349, ISO 1585) and may be modified without prior notice.

Focus on accessories



Rotor Ø 350, 80-65 cm
16 spikes
Fixed coupling
Support wheel included
Code **69219077**



Adjustable tool holder
Code **Z0020172**




WITH ROTARY CULTIVATOR

Gearbox/ Speed (km/h):

5-speed (4 forward + 1 reverse) with 6.50/80-12" wheels

Speed (km/h)	1.08	1	1R	2.82
	2.02	2		
	3.61	3		
	7.91	4		

Dimensions (mm)



L1	2180
L2	730
L3	1450
H1	600-1300
W1	420-510
W2	600-900



WITH CUTTERBAR MOWER

Gearbox/ Speed (km/h):

5-speed (4 forward + 1 reverse) with 6.50/80-12" wheels

Speed (km/h)	1.08	1	1R	2.82
	2.02	2		
	3.61	3		
	7.91	4		

Dimensions (mm)



L1	2185
L2	1125
L3	1060
H1	700-1300
W1	430-490
W2	1150-1600

Transmission	with oil-bath gearbox
Clutch	dry multidisc or mono-disc
Handlebars	with vertical and horizontal adjustment and 180° reversible, with vibration-damping device
Reverse gear	yes, with lever alongside gearbox
Differential	yes
Brakes	yes
Power take-off	2 power take-offs: one independent 2-speed PTO (1° 540 rpm - 2° 900 rpm) and one synchronised PTO
Accessories installation	with flange on PTO
Towing hitch	yes
Cowling	yes, with integral tool compartment/battery box
Weight	250 kg (with diesel engine, rotor and wheels)

Accessories



417 S

Accessory	Optional accessory			
Rotors for engines < 11 HP				
 <p>Rotor Ø 320, (80)-70-60-(50) cm 20 spikes Fixed coupling Support wheel included (expandable to 80 cm with kit 69210231) (can be reduced to 50 cm with kit 69210229)</p>	<p>69219070</p>		<p>Rear-mounted furrowing tool</p>	<p>L0009800</p>
 <p>Rotor Ø 320, 80-70-60-(50) cm 24 spikes Fixed coupling Support wheel included (can be reduced to 50 cm with kit 69210229)</p>	<p>69219068</p>		<p>Rear-mounted furrowing tool</p>	<p>L0009800</p>
Rotors for engines > 11 HP				
 <p>Rotor Ø 350, 80-65 cm 20 spikes Fixed coupling Support wheel included</p>	<p>69219076</p>		<p>Rear-mounted furrowing tool</p>	<p>Z0020134</p>
 <p>Rotor Ø 350, 80-65 cm 16 spikes Fixed coupling Support wheel included</p>	<p>69219077</p>		<p>Rear-mounted furrowing tool</p>	<p>Z0020134</p>

Accessories



Accessory		Optional accessory		
Tyred wheels				
 <p>Pair of tyred wheels 5.00x10" Adjustable disc</p>	69209003B		Pair of 15 kg ballasts (not compatible with adjustable half-shafts)	69209099
			Pair of 15 kg ballasts (compatible with adjustable half-shafts)	Z0020321
			Screw-adjustable half-shafts	69209105
			5-hole adjustable half-shafts	L0059500
			Pair of spacers L 95 mm	69209095
			Pair of snow chains	L0030200
 <p>Pair of tyred wheels 5.00x12" Adjustable disc</p>	69209002B		Pair of ballasts 25 kg (compatible with adjustable half-shafts)	69209077
			Screw-adjustable half-shafts	69209105
			5-hole adjustable half-shafts	L0059500
			Pair of spacers L 95 mm	69209095
 <p>Pair of tyred wheels 6.5/80x12" Adjustable disc</p>	69200038B		Pair of ballasts 25 kg (compatible with adjustable half-shafts)	69209077
			Screw-adjustable half-shafts	69209105
			5-hole adjustable half-shafts	L0059500
			Pair of spacers L 95 mm	69209095

Accessories



417 S

Accessory		Optional accessory		
Steel wheels				
 <p>Pair of steel wheels Ø 570x125 mm</p>	69209068		Pair of width adjustment rings W 100 mm	69209069
			Screw-adjustable half-shafts	69209105
			5-hole adjustable half-shafts	L0059500
			Pair of spacers L 95 mm	69209095
Adjustable tool holder				
 <p>Adjustable tool holder</p>	Z0020172		Single share plough	Z0020102
			180° turnwrest plough	Z0020104
			Furrowing tool	Z0020133
			Fixed-tine cultivator (not compatible with 5.00x10" wheels)	L0010200
			Potato digger (not compatible with 5.00x10" wheels)	L0066400
Drives and Cutter plates				
 <p>Oil-immersed drive</p>	L0101500		1.15 m Complete central cutter plate Semi-fine teeth	69229085
			1.27 m Complete central cutter plate Semi-fine teeth	69229086
			1.40 m Complete central cutter plate Semi-fine teeth	69229087
			0.95 m Complete central cutter plate Special teeth	69229068
			1.15 m Complete central cutter plate Special teeth	69229069
			1.27 m Complete central cutter plate Special teeth	69229070
			1.40 m Complete central cutter plate Special teeth	69229071
			Ballast for oil-immersed drive	L0105700
			Directional guides for semi-fine tooth cutter plate	69229064
Lighting				
 <p>Supplementary worklight kit (versions with electric starting only)</p>	69209113			