

# Rotary cultivator for home use

401 S

NEW



Designed for demanding home gardeners tending an allotment or vegetable plot, this rotary cultivator is extremely functional and offers the optimal combination of ease of use and safety.



Handlebar-mounted PTO control.



Handlebars with vertical and horizontal adjustment and 180° reversible, with vibration-damping device to assure more comfortable handling.



Integral QuickFit coupling that allows the operator to change the tools without using tools.

Power supply	Engine	Model	Displacement	Power*	Starting	Code
	POWERED by HONDA	GX 160 OHV	163 cm³	4.8 HP	recoil start	68319100EN
	Emak	K 800 H OHV	182 cm³	5.7 HP	recoil start	68319102EN

\* Engine power data refers to the values declared by each manufacturer. These values are calculated in accordance with specific measurement standards (such as SAE J1940, SAE J1349, ISO 1585) and may be modified without prior notice.

## Focus on accessories



**Rotor Ø 280, 50-(35) cm**  
12 spikes  
coupling for **Quickfit**  
(can be reduced to 35 cm with kit **L0116300**)  
Code **69219110**



**Rear-mounted furrowing tool**  
Code **L0050600**



**Brush L 80 - Ø 35 cm**  
With horizontal  
and vertical adjustment  
Code **L0070000**





## WITH ROTARY CULTIVATOR

**Gearbox/ Speed (km/h):**

**2-speed (1 forward + 1 reverse) with 4.00-8" wheels**

Speed (km/h) 1.18 **1** **1R** 3.07

## Dimensions (mm)



L1	1440
L2	470
L3	970
H1	230-1050
W1	380
W2	350-600



## WITH CUTTERBAR MOWER

**Gearbox/ Speed (km/h):**

**2-speed (1 forward + 1 reverse) with 4.00-8" wheels**

Speed (km/h) 3.07 **1** **1R** 1.18

## Dimensions (mm)



L1	1465
L2	600
L3	865
H1	345-1150
W1	380
W2	900-1117

Transmission	with oil-bath gearbox
Clutch	dry multidisc
Handlebars	with vertical and horizontal adjustment and 180° reversible, with vibration-damping device
Reverse gear	no
Differential	no
Brakes	no
Power take-off	independent 1004 rpm
Accessories installation	Integral QuickFit supplied as standard
Towing hitch	optional
Cowling	no
Weight	75 kg (with diesel engine, rotor and wheels)

## Accessories









## 401 S

Accessory		Optional accessory		
Rotors				
 <p>Rotor Ø 280, <b>50</b>-(35) cm 12 spikes coupling for <b>Quickfit</b> (can be reduced to 35 cm with kit <b>L0116300</b>)</p>	69219110		Support wheel	Z0020368
			Rear-mounted furrowing tool	L0050600
 <p>Rotor Ø 280, <b>60</b>-50-(35) cm 16 spikes coupling for <b>Quickfit</b> (can be reduced to 35 cm with kit <b>L0116300</b>)</p>	69219107		Support wheel	Z0020368
			Rear-mounted furrowing tool	L0050600
Tyred wheels				
 <p>Pair of tyred wheels <b>4.00x8"</b> <b>Fixed disc</b> Quickfit coupling</p>	69209020A		Pair of snow chains	L1055015
			Pair of spacers <b>L 100 mm</b>	69209096
Steel wheels				
 <p>Pair of steel wheels Ø <b>370 mm</b></p>	L0051200			

## Accessories



Accessory		Optional accessory			
Towing hitch					
	Towing hitch	L0060900			
Adjustable tool holder					
	Adjustable tool holder (requires towing hitch <b>L0060900</b> )	L0103400		Single share plough	L0100000
				Furrowing tool	L0103200
Bar drive					
	Cam drive	69229091		0.92 m Complete central cutter plate <b>Special teeth</b>	69222011
Front brush					
	Brush <b>L 80-Ø 35</b> cm With horizontal and vertical adjustment	L0070000			